

### **Amendments to the Claims**

This listing of claims will replace all prior versions, and listings, of claims in the application.

### **Listing of Claims**

1. (Currently Amended) An ablation catheter comprising:  
  
a tubular body having a distal end region, the tubular body defining at  
  
least a partial curve along the distal end region of the tubular body, the  
  
partial curve being adapted to change curvature; and  
  
at least one ablating electrode arranged along the at least partial curve, the at  
  
least one electrode being adapted to change curvature along with the at  
  
least partial curve along the distal end region of the tubular body,  
  
wherein the at least one electrode is configured to be flexible and resilient.
2. (Canceled).
3. (Currently Amended) The ablation catheter of claim 1 ~~2~~ ~~wherein the at least one~~  
~~electrode comprises at least one flexible and resilient electrode strand~~ further  
comprising a flexible and resilient shaping element.
4. (Currently Amended) The ablation catheter of claim 1 ~~3~~ wherein the at least one  
flexible and resilient electrode ~~strand~~ is comprised, at least partially, of material selected  
from the group consisting of platinum, gold, stainless steel, and composite of conductive  
polymer metal.
5. (Currently Amended) The ablation catheter of claim 1 ~~2~~ wherein the at least one  
electrode ~~strand~~ defines a saw tooth pattern.

6. (Currently Amended) The ablation catheter of claim 1 2 wherein the at least partial curve defines an outside radius, and wherein the at least one electrode ~~strand~~ defines a first end region and a second end region, and wherein the first end region is coupled with a point along the outside radius of the at least partial curve and wherein the second end region is coupled with a second point along the outside radius of the at least partial curve along the distal end region of the tubular body.

7. (Currently Amended) The ablation catheter of claim 1 2 wherein the at least one electrode ~~strand~~ further defines an elastically deformable electrode ~~strand~~.

8. (Currently Amended) The ablation catheter of claim 7 wherein the at least one elastically deformable electrode strand ~~strand~~ is biasedly coupled with the at least partial curve along the distal end region of the tubular body.

9. (Currently Amended) The ablation catheter of claim 8 wherein the biased connection of the at least one elastically deformable electrode strand ~~strand~~ is biased to change the curvature of the at least partial curve along the distal end region of the tubular body.

10. (Original) The ablation catheter of claim 1 wherein the at least partial curve along the distal end region of the tubular body defines a closed loop.

11. (Original) The ablation catheter of claim 1 wherein the at least partial curve along the distal end region of the tubular body defines an open loop.

12. (Currently Amended) The ablation catheter of claim 1 ~~2~~ wherein the at least one electrode includes at least one electrode strand interlaced along the at least partial curve along the distal end region of the tubular body.

13. (Original) The ablation catheter of claim 12 wherein the at least partial curve defines an outside surface, and wherein the at least one electrode strand is interlaced along the outside surface.

14. (Previously presented) The ablation catheter of claim 12 wherein the at least partial curve defines an inside surface, and wherein the at least one electrode strand is interlaced along the inside surface.

15. (Previously presented) The ablation catheter of claim 13 wherein the at least one electrode strand is interlaced along the outside circumference such that the electrode strand is intermittently exposed along the outside circumference.

16. (Original) The ablation catheter of claim 15 wherein:

the at least one electrode strand defines a first length of the at least one strand, the first length defining intermittently exposed sections of the at least one electrode strand; and

the at least one electrode strand further defines a second length of the at least one strand, the second length defining intermittently exposed sections of the at least one electrode strand.

17. (Original) The ablation catheter of claim 16 wherein the first length of the at least one strand and the second length of the at least one strand cooperate to define a generally continuously exposed segment of the at least one strand.

18. (Previously presented) The ablation catheter of claim 17 wherein the generally continuously exposed segment of the at least one strand is coupled with a power supply and adapted to be energized thereby during an ablation procedure.

19. (Currently Amended) An ablation catheter comprising a tubular shaft defining a distal end region, the tubular shaft further defining at least a partial curve along the distal end region;

flexible and resilient electrode means for conveying ablation energy to a target tissue, the flexible and resilient electrode means arranged along the at least partial curve along the distal end region of the tubular shaft.

Application No: 10/613,794

Response to Office action dated August 7, 2007 and Advisory action dated

Amendment and Response Accompanying Request for Continued Examination Under 37 C.F.R. § 1.114 dated December 17, 2007

20. (Currently Amended) The ablation catheter of claim 19 wherein the means for conveying ablation energy to a target tissue comprises at least one electrode ~~strand~~ arranged in a flexible and resilient configuration along some portion of the at least partial curve along the distal end region of the tubular shaft.